

# Material Safety Data Sheet

according to Directive 1907/2006/EC (REACH) and 453/2010/EU

Printing date: 28.05.2014

Date of issue: 24.04.2014

Page: 1/9

## 1 Identification of the Substance/Mixture and of the Company

### 1.1 Product identifier

REF 91324  
 Product name QUANTOFIX Calcium / 60  
 1 x 6 g Calcium-1  
 1 x 30 mL Calcium-2  
 60 x Test strips

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product for analytical use.  
 Exposure Scenario Classification according REACH, RIP 3.2 Codes: SU 0-2, PC 21, PROC 15, AC 0  
 The exposure scenario is integrated into sections 1-16.

### 1.3 Details of the supplier of the safety data sheet

**Manufactured by:**  
 MACHEREY-NAGEL GmbH & Co. KG  
 Neumann-Neander-Str. 6-8, 52355 Dueren, GERMANY  
 Tel.: +49 2421 969 0 E-mail: msds@mn-net.com

### 1.4 Emergency telephone number

Outside Germany (DE): Call your regional Poisons Information Service or call local Life Saving Service.  
 DE: Gemeinsames Giftinformationszentrum (GGIZ) 99089 Erfurt tel. +49 361 730 730

*Missing subsections are not relevant for the risk assessment of the product and may be omitted programmatically.*

## 2 Hazard Identification

### 2.1 Classification of the substance(s) or mixture(s) - in the complete product

**Directive 1999/45/EC**  
 Symbols



C  
 R 35

R

**CLP Directive 1272/2008/EC**  
 GHS pictograms



GHS03



GHS05



GHS07

Signal word

DANGER

**Hazard identification**

**Hazard classes/categories**

H272	Ox. Liq. 2
H314	Skin Corrosion 1A. Serious Damage to Eyes 1
H315	Skin Irrit. 2
H318	Eye Dam. 1
H335	STOT SE 3

### 2.2 Hazard Description

**Possible Hazards from physicochemical Properties**

Generally in the case of pH values are less than 2 or higher than 11.5 then it is corrosive. In the case of pH values are less than 5 or higher than 9 then it is irritant.

**Information pertaining to particular Risks to Human and possible Symptoms**

Causes varying degrees of acid burns on the skin, to the eyes and to the mucous membranes and wounds which do not heal quickly depending on the concentration, temperature and the exposure time. Vapours especially which steam from hot liquids and mist can have a severe irritant effect upon the eyes and the respiratory organs.

# Material Safety Data Sheet

according to Directive 1907/2006/EC (REACH) and 453/2010/EU

Printing date: 28.05.2014

Date of issue: 24.04.2014

Page: 2/9

**Information pertaining to particular Risks to the Environment**

--- Avoid contact of substance/mixture to environment. ---

**Other Hazards**

---

## 2.3 Other hazards: Description of the components

### 6 g Calcium-1

Directive 1999/45/EC

Symbols

R 41



Xi

CLP Directive 1272/2008/EC

GHS pictograms



GHS03

GHS05

GHS07

Signal word

DANGER

**Hazard identification**

**Hazard classes/categories**

H272

Ox. Liq. 2

H315

Skin Irrit. 2

H318

Eye Dam. 1

H335

STOT SE 3

### 30 mL Calcium-2

Directive 1999/45/EC

Symbols

R 35



C

CLP Directive 1272/2008/EC

GHS pictograms



GHS05

Signal word

DANGER

**Hazard identification**

**Hazard classes/categories**

H314

Skin Corrosion 1A. Serious Damage to Eyes 1

### Test strips

Directive 1999/45/EC

Symbols

-  
do not need labelling as hazardous

CLP Directive 1272/2008/EC

GHS pictograms

do not need labelling as hazardous

Signal word

do not need labelling as hazardous

No hazard class

# Material Safety Data Sheet

according to Directive 1907/2006/EC (REACH) and 453/2010/EU

Printing date: 28.05.2014

Date of issue: 24.04.2014

Page: 3/9

## 3 Composition/Information on Ingredients

### 3.1 Substances or 3.2 Mixtures

#### 6 g Calcium-1

Chemical:	<i>hydrogen peroxide urea</i>	CAS No.:	124-43-6
Concentration:	80 - 100 %		
Formula:	CH <sub>4</sub> N <sub>2</sub> O•H <sub>2</sub> O <sub>2</sub>		
Pseudonym:	Percarbamide		
EC No.:	204-701-4		
RTECS:	YT4860000	MFCD:	00013119
TSCA Inventory:	listed		
acc. 1999/45/EC:	R 37/38-41	acc. CLP (GHS):	H272, H315, H318, H335

#### 30 mL Calcium-2

Chemical:	<i>sodium hydroxide solution</i>	CAS No.:	1310-73-2
Concentration:	20 - 55 %		
Formula:	NaOH•H <sub>2</sub> O		
Pseudonym:	soda lye		
REACH Reg. No.:	01-2119457892-27-xxxx		
EC No.:	215-185-5	Indice No.:	011-002-00-6
RTECS:	WB4900000		
TSCA Inventory:	listed		
acc. 1999/45/EC:	R 35	acc. CLP (GHS):	H314

#### Test strips

Chemical:	<i>cellulose</i>	CAS No.:	9004-34-6
Concentration:	1 - 10 %		
Formula:	(C <sub>6</sub> H <sub>10</sub> O <sub>5</sub> ) <sub>n</sub>		
REACH Reg. No.:	exempt, Annex IV		
EC No.:	232-674-9		
RTECS:	FJ5691460		
TSCA Inventory:	listed		
acc. 1999/45/EC:	-	acc. CLP (GHS):	not necessary

Chemical:	<i>chemicals/mixture &lt; 1%, no declaration necessary</i>	CAS No.:	-
Concentration:	0,1 - 1 %		
acc. 1999/45/EC:	-	acc. CLP (GHS):	not necessary

Chemical:	<i>PVC foil (CAS 9002-86-2)</i>	CAS No.:	-
Concentration:	95 - 100 %		
acc. 1999/45/EC:	-	acc. CLP (GHS):	not necessary

### 3.2 Remarks

List of R and H phrases: see chapter 16

## 4 First Aid Measures

### 4.1 Description of first aid measures

Place insured person out of danger zone to fresh air immediately. Ensure quiet, warmth, and provide resuscitation if necessary. If necessary contact medical advice. Remove contaminated clothing. Show product package, packing insert and this material safety data sheet to the doctor.

#### 4.1.1 After SKIN Contact

Remove dust with wetted tissue. Remove contaminated clothing immediately. Rinse the affected skin or mucous membrane thoroughly for min. 15 minutes under running water. (If possible) use soap. Avoid neutralisation. Then apply a loose bandage.

#### 4.1.2 After EYE Contact

Rub dust with teardrops from eyes or: After contact with the eyes rinse thoroughly under running water with the eyelid wide open for min. 10 minutes with eye washing bottle, eye douche or running water (protect intact eye). Before (if possible) apply eye drops Proxymetacaine 0.5%, if the opening the eyelid convulsion is painful. Further treatment to be carried out by an eye specialist.

#### 4.1.3 After INHALATION of Vapours

After inhalation of foam or vapour fresh air should be inhaled. Keep airways free. If vomiting and if insensible place patient in recovery position and keep airways free. After inhalation of dust fresh air should be inhaled.

#### 4.1.4 After ORAL Intake

# Material Safety Data Sheet

according to Directive 1907/2006/EC (REACH) and 453/2010/EU

Printing date: 28.05.2014

Date of issue: 24.04.2014

Page: 4/9

After oral intake lots of water with activated charcoal supplement should be drunk after it has been ingested. Do not induce vomiting under any circumstances. Do not make any efforts to neutralise it. Contact medical advice for possible consequences.

## 4.2 Indication of any immediate medical attention and special treatment needed

**CORROSIVE DAMAGE:** After SKIN CONTACT rinse with water for a long time. Efforts to neutralise the substance can frequently make matters worse. Apply glucocorticosteroides following inflammatory reactions. After EYE CONTACT rinse immediately with plenty of water for a long time. Eyelid convulsion measures. Name the corrosive chemical. Further treatment must be carried out by an eye specialist. After INTAKE administer aluminium oxide drug suspensions. Administer a prophylaxis to counter pulmonary oedema following the INGESTION of corrosive aerosols. In the event of RESPIRATORY DISTRESS ensure that the patient inhales oxygen.

## 5 Firefighting Measures

### 5.1 Extinguishing media

Fire extinguishers appropriate to the fire classification, and, if applicable, a fire blanket must be available in a prominent location in the work area. All extinguishers like FOAM, WATER SPRAY, DRY POWDER, CARBON DIOXIDE can be used.

### 5.2 Special hazards arising from the substance or mixture

Formation of hazardous and caustic vapour-air mixtures possible. Danger for environment **only in the event of a large-scale leakage** or formation of hazardous substances.

### 5.3 Advice for firefighters

No, for listed product. Product package burns like paper or plastic. Spray any vapours released with water. Retent fire water. Use only acid-resistant safety equipment.

For great amount - if necessary - protective breathing apparatus which is independent of the ambient air (isolated equipment), and sealed protective clothing is necessary in the event of a large-scale formation of toxic substances.

### 5.4 Additional Information

---

## 6 Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear suitable protective gloves (see 8.2.2). Wear eye protection, respectively face protection. Regular staff training is necessary, indicating hazards and precautions on the basis of operating instructions. Restrictions on activity must be observed.

### 6.2 Methods and material for containment and cleaning up

Bind any escaping liquid with inert absorbent. And dispose in accordance to local regulations for the disposal of hazardous chemicals. Clean any contaminated equipment and floors with plenty of water. Collect small amounts of leaked liquid and flush with water into drains.

## 7 Handling and Storage

### 7.1 Precautions for safe handling

Handling in accordance with the test instruction, that comes with the product.

### 7.2 Conditions for safe storage, including any incompatibilities

The original product package of MACHEREY-NAGEL allows a safe storage. Storage class (German chemical industry): see chapter 12.1

#### 7.2.1 Requirements for Stock Rooms and Containers

Keep original product packages tightly closed during handling and storage. Use inbreakable container for transport of glass bottles.

## 8 Exposure Controls/Personal Protection

### 8.1 Control parameters

#### 6 g Calcium-1

Chemical: *hydrogen peroxide urea*

CAS No.: 124-43-6

TRGS 900 (DE):  $H_2O_2$  1 ppm / 1,4 mg/m<sup>3</sup>  
E/e respirable

SUVA(CH) MAK value:  $H_2O_2$  1 ppm / 1,4 mg/m<sup>3</sup>

TRGS 905 (DE): K4, R<sub>F</sub> C

TSCA Inventory: listed

#### 30 mL Calcium-2

Chemical: *sodium hydroxide solution*

CAS No.: 1310-73-2

TRGS 900 (DE): (2 E) mg/m<sup>3</sup>

E/e respirable

Short-term exposure factor: =1=

[www.mn-net.com](http://www.mn-net.com)



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

Germany  
and international:

Tel.: +49 24 21 969-0  
Fax: +49 24 21 969-199  
E-mail: [info@mn-net.com](mailto:info@mn-net.com)

Switzerland:

MACHEREY-NAGEL AG

Tel.: +41 62 388 55 00  
Fax: +41 62 388 55 05

E-mail: [sales-ch@mn-net.com](mailto:sales-ch@mn-net.com)

France:

MACHEREY-NAGEL EURL

Tel.: +33 388 68 22 68  
Fax: +33 388 51 76 88

E-mail: [sales-fr@mn-net.com](mailto:sales-fr@mn-net.com)

USA:

MACHEREY-NAGEL Inc.

Tel.: +1 484 821 0984  
Fax: +1 484 821 1272

E-mail: [sales-us@mn-net.com](mailto:sales-us@mn-net.com)

# Material Safety Data Sheet

according to Directive 1907/2006/EC (REACH) and 453/2010/EU

Printing date: 28.05.2014

Date of issue: 24.04.2014

Page: 5/9

skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value:	2 e mg/m <sup>3</sup>	
Australia NICNAS:	not listed	Canada CEPA 1999: DSL Yes
Japan CSCL/PRTR:	not listed	
Japan PDSCL:	not listed	Japan ISHL: Article 57-2 (SDS required)
South Korea TCCA:	not listed	
TSCA Inventory:	listed	California Proposition 65 List: not listed
NIOSH:	2 mg/m <sup>3</sup>	
OSHA:	TWA 2 mg/m <sup>3</sup>	

### Test strips

Chemical:	<i>cellulose</i>	CAS No.: 9004-34-6
TRGS 900 (DE):	Staub 4 E mg/m <sup>3</sup> E/e respirable	

SUVA(CH) MAK value:	3 a ppm	
Australia NICNAS:	not listed	Canada CEPA 1999: DSL yes
Japan CSCL/PRTR:	not listed	
Japan PDSCL:	not listed	Japan ISHL: not listed
South Korea TCCA:	not listed	
TSCA Inventory:	listed	California Proposition 65 List: not listed
NIOSH:	not listed	
OSHA:	not listed	

Chemical: *chemicals/mixture < 1%, no declaration necessary* CAS No.: -

Chemical: *PVC foil (CAS 9002-86-2)* CAS No.: -

## 8.2 Exposure controls

The highest level of cleanliness must be maintained at the workplace.

### 8.2.1 Respiratory Protection

Only if additional recommendations in test instruction or packing insert.

### 8.2.2 Hand Protection

Yes, gloves according EN 374 (permeation time >30 min - level 2), consist of PVC, natural latex, Neopren, or Nitril (f.ex. from Ansell or KCL). Use for short times chemical resistant latex gloves with code EN 374-3 level 1.

### 8.2.3 Eye Protection

Yes, safety glasses according EN 166 with integrated side shields or wrap-around protection or face protection.

### 8.2.4 Skin Protection

Recommended to avoid clothing damage, and to avoid contamination with these hazards.

### 8.2.5 Personal Hygiene

Eating, drinking, smoking, taking snuff and storage of food in work areas and at outdoor workplaces is prohibited. Avoid contact with the skin, eyes and clothing. Rinse any clothing on which the substance has been spilled, and soak it in water. Wash hands thoroughly with soap and water when stopping work and before eating, and then apply protective skin cream.

## 9 Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

#### 6 g Calcium-1

Color: colourless      Odor: odorless      Appearance: powder (solid)

#### 30 mL Calcium-2

Color: colourless      Odor: odorless      Appearance: liquid

#### Test strips

Color: colored      Odor: odorless      Appearance: solid

### 9.2 Other information

#### 9.2.1 Safety relevant Basis Data

##### 6 g Calcium-1

pH: 4  
Specific gravity: 1,39 sol.  
Solubility in water: 0-100 %  
Melting point: 75-85 instable °C

# Material Safety Data Sheet

according to Directive 1907/2006/EC (REACH) and 453/2010/EU

Printing date: 28.05.2014

Date of issue: 24.04.2014

Page: 6/9

30 mL Calcium-2  
 pH: 14  
 Specific gravity: 1,35 g/mL  
 Solubility in water: 0-100 %

Test strips

## 9.2.2 Relevant Properties of Substance Group

---

## 9.3 Additional Information

not necessary

## 10 Stability and Reactivity

### 10.1 Conditions to avoid

If on label. When indicated in packing insert.

### 10.2 Incompatible materials

Avoid contact with concentrated acids and oxidizing agents. Avoid contact with strong acids or alkalines.

### 10.3 Hazardous decomposition products

In the original package all parts/all reagents are safety and separated stored. Decompositions are not observed during the expiration period under recommended conditions.

## 11 Toxicological information

### 11.1 Information on toxicological effects

Following information is valid for pure substances. Quantitative data on the toxicity of this product are not available.

#### 6 g Calcium-1

Chemical: *hydrogen peroxide urea* CAS No.: 124-43-6  
 LD50<sub>orl rat</sub>: >2000 mg/kg

#### 30 mL Calcium-2

Chemical: *sodium hydroxide solution* CAS No.: 1310-73-2  
 LD50<sub>orl rat</sub>: 500<sub>100%</sub> mg/kg  
 LD50<sub>orl mus</sub>: 40 mg/kg

#### Test strips

Chemical: *cellulose* CAS No.: 9004-34-6  
 LD50<sub>orl rat</sub>: >5000 mg/kg  
 LC50<sub>ihl rat</sub>: >5800<sub>4h</sub> mg/m<sup>3</sup>  
 LD50<sub>drm rbt</sub>: >2000 mg/kg

Chemical: *chemicals/mixture < 1%, no declaration necessary* CAS No.: -

Chemical: *PVC foil (CAS 9002-86-2)* CAS No.: -

## 12 Ecological information

### 12.1 Toxicity

Following information is valid for pure substances.

#### 6 g Calcium-1

Chemical: *hydrogen peroxide urea* CAS No.: 124-43-6  
 WGK (DE): 1 WGK No.: (0288H<sub>2</sub>O<sub>2</sub>)  
 Storage class (VCI): 5.1 B

#### 30 mL Calcium-2

Chemical: *sodium hydroxide solution* CAS No.: 1310-73-2  
 LC50<sub>leuciscus idus/96h</sub>: 35-189 mg/L  
 LC50<sub>fish/96h</sub>: 45.4 mg/L  
 EC50<sub>daphnia/48h</sub>: >100 mg/L  
 WGK (DE): 1 WGK No.: 0142  
 Storage class (VCI): 8 B

www.mn-net.com



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

Germany  
 and international:  
 Tel.: +49 24 21 969-0  
 Fax: +49 24 21 969-199  
 E-mail: info@mn-net.com

Switzerland:  
 MACHEREY-NAGEL AG  
 Tel.: +41 62 388 55 00  
 Fax: +41 62 388 55 05  
 E-mail: sales-ch@mn-net.com

France:  
 MACHEREY-NAGEL EURL  
 Tel.: +33 388 68 22 68  
 Fax: +33 388 51 76 88  
 E-mail: sales-fr@mn-net.com

USA:  
 MACHEREY-NAGEL Inc.  
 Tel.: +1 484 821 0984  
 Fax: +1 484 821 1272  
 E-mail: sales-us@mn-net.com

# Material Safety Data Sheet

according to Directive 1907/2006/EC (REACH) and 453/2010/EU

Printing date: 28.05.2014

Date of issue: 24.04.2014

Page: 7/9

## Test strips

Chemical:	cellulose	CAS No.:	9004-34-6
WGK (DE):	nwg		
Storage class (VCI):	11		
Chemical:	chemicals/mixture < 1%, no declaration necessary	CAS No.:	-
WGK (DE):	1		
Chemical:	PVC foil (CAS 9002-86-2)	CAS No.:	-

## 13 Disposal Considerations

Please observe local regulations for collection and disposal of hazardous waste and contact waste disposal company, where you will obtain information on laboratory waste disposal (waste code number 16 05 06).

### 13.1 Waste treatment methods

Empty containers of corrosive reagents prior to disposal, rinse with water.

## 14 Transport Information

14.1 UN No.:	<b>3316</b>	14.2 Proper shipping name:	<b>Chemical Kit</b>
14.3 Class:	<b>9</b>	14.4 Packing group:	<b>II</b>
<i>Road transport</i>			
Classification code:	M11	Tunnel restriction code:	E
Limited Quantity:	LQ 0 (acc. ADR 3.3.1/251: see LQ in Alternative Transport Labelling)		
<i>Air transport</i>			
PAX:	960	max. weight PAX:	10 KG
CAO:	960	max. weight CAO:	10 KG
<i>Maritime transport</i>			
EmS:	F-A, S-P	Storage category:	A

### Alternative Transport Labelling follows:

Class 8 II, **excepted quantities** ( $\leq 30 \text{ mL} / \Sigma \leq 500 \text{ mL}$ ) = ADR/ IATA E2

14.1 UN No.:	<b>3266</b>	14.2 Proper shipping name:	<b>Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide solution)</b>
14.3 Class:	<b>8</b>	14.4 Packing group:	<b>II</b>
<i>Road transport</i>			
Classification code:	C5	Tunnel restriction code:	E
Limited Quantity:	LQ22		
Excepted Quantity:	E 2		
<i>Air transport</i>			
PAX:	851	max. weight PAX:	1 L
CAO:	855	max. weight CAO:	30 L
<i>Maritime transport</i>			
EmS:	F-A, S-B	Storage category:	B

## 15 Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

German act governing protection from hazardous substances (Chemicals Act / Chemikaliengesetz- ChemG), revised on August 2013  
 German order governing protection from hazardous substances (Ordinance on Hazardous Substances / Gefahrstoffverordnung - GefStoffV), revised on November 2010, according to Directive 98/24/EC  
 TRGS 200, German engineering rules governing the classification and labelling of hazardous substances, preparations and products, updated October 2011  
 Announcement BekGS 220 (DE), Safety Data Sheet, June 2013

According 1999/45/EC small amounts of harmful and highly flammable preparations/mixtures have partly/completely exemption from labelling (no symbols F, O, Xn, Xi, N and no R and S phrases are necessary) until **25-125 mL/g** .

According **GHS** inner packages must be only labelled with symbol(s) and product identifier.  
 Harmful chemicals/mixtures with signal word: **WARNING** and highly flammable chemicals/mixtures must not be labelled with H and P phrases until **125 mL** or **125 g**.  
 Oxidizing mixtures with signal word: **DANGER** and **H272** must not be labelled with H and P phrases until **125 mL** .

# Material Safety Data Sheet

according to Directive 1907/2006/EC (REACH) and 453/2010/EU

Printing date: 28.05.2014

Date of issue: 24.04.2014

Page: 8/9

## 6 g Calcium-1

Directive 1999/45/EC

Symbols:



Xi  
R 41  
Risk of serious damage to eyes.

S 26-39

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear eye/face protection.

CLP Directive 1272/2008/EC

GHS pictograms:



GHS03



GHS05



GHS07

Signal word: DANGER

H318  
Causes serious eye damage.

P280sh, P305+351+338

Wear protective gloves/eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## 30 mL Calcium-2

Directive 1999/45/EC

Symbols:



C  
R 35  
Causes severe burns.

S 26-37/39-45

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

CLP Directive 1272/2008/EC

GHS pictograms:



GHS05

Signal word: DANGER

H314  
Causes severe skin burns and eye damage.

P260D, P280sh, P301+330+331, P303+361+353, P304+340, P305+351+338, P501

Do not breathe vapours. Wear protective gloves/eye protection. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents/container to regulated waste treatment.



# Material Safety Data Sheet

according to Directive 1907/2006/EC (REACH) and 453/2010/EU

Printing date: 28.05.2014

Date of issue: 24.04.2014

Page: 9/9

## Test strips

Directive 1999/45/EC

Symbols:

-  
-

S 22

Do not breathe dust.

CLP Directive 1272/2008/EC

GHS pictograms:

do not need labelling as hazardous

Signal word: -

## 15.2 Chemical safety assessment not necessary for these small amounts

## 16 Other Information

### 16.1 List of R and H phrases

#### 16.1.1 List of relevant R phrases

R35 Causes severe burns.  
R37/38 Irritating to respiratory system and skin.  
R41 Risk of serious damage to eyes.

#### 16.1.2 List of relevant H phrases

H272 May intensify fire; oxidizer.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.

### 16.2 Training Advice

Multiple safety training of staffs about danger and protection by using hazards in working area. Additionally training and introduction of staffs for using these products.

### 16.3 Recommended Restriction on Use

Only for professional user.

Look about employee restrictions for young people (f. ex. 94/33/EC or DE § 22 JArbSchG)!

Look about employee restrictions for pregnant women and nursing women (f.ex. 92/85/EEC or DE §§ 4 und 5 MuSchRiV)!

An individual package of this product or test kit has a moderate hazardous potential.

### 16.4 Further Information

MACHEREY-NAGEL GmbH & Co. KG provides the information contained herein in good faith being up-to-date of own realizations at revision time. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose.

MACHEREY-NAGEL GmbH & Co. KG makes NO REPRESENTATIONS or WARRANTIES, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly MACHEREY-NAGEL GmbH & Co. KG will not be responsible for damages resulting from use of or reliance upon this information. See terms and conditions at the end of our price lists for additional information.

### 16.5 Sources of Key Data

Regulation 453/2010/EU REACH - REQUIREMENTS FOR THE COMPILATION OF SAFETY DATA SHEETS

Regulation 487/2013/EU, 4<sup>th</sup> adaptation of CLP regulation to technical and scientific progress

TRGS 900, German engineering rules governing limits in air at work, updated July 2012

SUVA .CH, Limits in air at work 2009, revised on 01.2009

KÜHN, BIRETT Merkblätter Gefährliche Arbeitsstoffe (Data Sheets of Hazardous Substances)

### 16.6. Revisions/Updates

Reason for Revision: 2014-02 Corrected structure of sections acc. regulation 453/2010/EU, if necessary

2014-04 Adaptation of regulation 487/2013/EU

You find our current versions of MSDS in Internet:

<http://www.mn-net.com/MSDS>